



GeoHome Family Tent
ICRC/IFRC/IOM Standard

Product key features GeoHome Family Tent

- New generation family tent, geodesic shape
- Adaptable to all climates
- Easy-set up (30 minutes, 3 persons)
- UV resistance, FR- and waterproof
- Accommodates five persons
- Rapid deployment in any emergency.

Technical specifications

Dimensions - GeoHome Family Tents

Outer tent	
Total living area	22.6 m ²
Centre height	2.40 m
Length	4.2 m
Width	5.38 m
Wall height	Dome-shaped
Door height	1.80 m (1.7 m inner tent)

Materials	
Outer tent (roof, walls, mud flaps, ground sheets and share fly)	Base fabric: Woven high-density polyethylene (HDPE) black fibres Coating: white low density polyethylene (LDPE) on both sides, 190 gsm, Fire retardancy: EN13823+AI
Mosquito nets	Polyester Outer tent: 7-9 holes per inch ² Inner tent: 20-25 holes per inch ²
Frame	All aluminium Main pipes: outer diameter 19 mm +/- 0.5 mm, thickness 1.2 mm +/- 1%, Connectors: outer diameter adapted to main pipe, thickness 1.5 mm +/- 1%

Tent parts	
Windows	Six windows. Two on each side of the tent and one next to each of the doors 500 mm x 500 mm Lower edge of the window 500 mm from the ground
Ventilation	Two ventilation openings at the top of the tent roof above the doors.
Mosquito nets	Polyester Outer tent: 7-9 holes per inch ² Inner tent: 20-25 holes per inch ²
Doors	Two doors located on the centre of both tent gable ends. 0.9 m wide x 1.7 m high

Packing & shipping

Packing unit	
Contents	Fly sheet, outer tent, inner tent with ground sheet, accessories and hammer. One tent is packed in PE bag with separate webbing bands plus handle.
Weight	48.50 kgs approx.
Dimension	112 x 40 x 45 cm
Volume	0.202 cbm approx.
Pallet	
Bales per pallet	4 pcs
Weight	210 kgs approx.
Dimension	115 x 78 x 110 cm
Volume	0.988 cbm approx.

Estimated loadability

Estimated loadability ¹		
Container	With pallet	Without pallet
20' DC container	24 pallets (96 pcs)	135 pcs
40' DC container	56 pallets (224 pcs)	270 pcs
40' HC container	56 pallets (224 pcs)	312 pcs

¹ The loadability provided is based on the maximum volume and weight capacity of the containers. This might change due to road weight restrictions in the country of destination. Please contact our sales team for further clarifications.