



Huggy™ 24 Tent



## Product key features

### Huggy™ 24 Tent

- Waterproof, rotproof and UV-stabilized
- Lightweight, rectangular and framed tent that can be used for schooling, storage or temporary shelter purposes (comes in three sizes)
- Outer tent fabric is made of 450 - 455 g/m<sup>2</sup> PVC coated fabric, natural white
- Marking and logo customised to your requirements.

#### Huggy™ 24 Tent

Total size of 6 m x 4 m

#### Technical specifications

#### Dimensions

Outer tent	
Total size	6.00 x 4.00 m
Centre height	2.80 m
Wall height	1.95 m
Inner tent	
Centre height	2.30 m
Wall height	1.80 m

Materials	
Outer tent	450 - 455 gsm fire retardant* PVC coated fabric 5000 mm, natural white
Inner tent	120 gsm Polycotton, natural white
Ground sheet	190 gsm Polyethylene (HDPE), PVC fabric, sewn in bathtub, light grey/natural white
Windows	Six windows on long sidewalls 0.85 x 0.85 m with PE stripes reinforcement Four windows on short sidewalls 0.70 x 0.85 m with PE stripes reinforcement
Doors	One door on each gable end side 1.00 x 1.80 m, closed with velcro
Ground sheet	Double stitched to inner tent, 100 - 200 mm above the ground
Main frame	35 aluminum pipes 37 mm diameter, 2 mm thick, silver / 10 steel connectors, silver / 12 steel connectors with base plates, silver / Four hanging steel connectors
Seams	All seams are double-stitched with welded main roof seams

## Packing & shipping

All contents are packed in a wooden box.

Contents	Package A	Package B	Estimated loadability <sup>1</sup>	
	One roof, two wall and two door panels, one inner tent, instruction sheet	35 frame pipes, 22 frame connectors, 10 pegs, 4 hanging connectors, 8 base plates, hammer, instruction sheet and repair kit	Container	Wooden crates
Weight per package	100 kg	95 kg	20' GP container	24 tents
Total weight	195 kg		40' DC container	50 tents
Volume per package	110 x 94 x 52 cm / 0.538 cbm	192 x 46 x 48 cm / 0.424 cbm	40' HC container	60 tents
Total volume	0.962 cbm			

<sup>1</sup> The loadability provided is based on the maximum volume and weight capacity of the containers. This might change due to road weight restrictions in the country of destination. Please contact our sales team for further clarifications.