



HuggyPRO 72 Tent



Product key features

HuggyPRO 72 Tent

- Innovative tent design with newly-engineered lightweight steel frame and high-performance laminated polyethylene cover
- Lightweight, multi-purpose tent for medical, educational, office or accommodation use
- Adaptable to different climate zones; high wind and snow load resistance
- Ideal for medical purposes, easy to clean with disinfectants
- All materials can be reused, recycled or safely disposed
- Also available in 24 and 42 m² floor space versions.

Technical specifications

General description

Construction	High tensile steel tubular frame with PE cover and floor
Entry	Two PE roll-up doors with zippers and buckles, and mosquito mesh walk-through door
Modularity	Connectable lengthwise to other HuggyPRO tents

Dimensions

Total size	72 m ²
Length	12.0 m
Width	6.0 m
Wall height	2.05 m
Central height	2.98 m

Materials	
Frame	Galvanised high tensile steel pipe, 38 mm Ø, 1.2 mm thickness, press formed steel joints
Outer cover	250 g/m ² laminated PE - UV resistant, rot-proof, fire resistant CPAI 84-6 – white colour
Floor	180 g/m ² laminated PE – UV resistant, rot-proof, fire resistant CPAI 84-6 – grey colour
Pegs	T-pegs, galvanised steel, 50 cm length

Optional accessories	
Marking and logos	Logos printed directly on to the tent upon request
LED light system	<p>Cost effective, high output LED light system that can be daisy-chained up to 10 lights. For worldwide use. Power input: 86-250V / 50 or 60 H</p> <ul style="list-style-type: none"> Materials: Aluminium casing with acrylic milk glass. IP54 weather resistance, IP54 weather resistance Packing: 800 g 130 x 5 x 6 (padded polyester bag)
Shade cover kit	<p>Laminated PE fabric and PE shade mesh, supported by steel wire cables tensioned horizontal over the tent roof</p> <ul style="list-style-type: none"> Materials: 180 g/m² laminated PE - UV resistant, rot-proof, flame retardant CPAI 84-6, white colour 180 g/m² HDPE knitted mesh – UV resistant, rotproof, flame retardant CPAI 84-6, black colour Support kit: Five sets of 4 mm steel wire cable, cable tensioner, 'bull horn' end fittings and distance poles Packing: 20 kg 70 x 70 x 35 cm (bale)
Inner tent	<p>Polycotton inner tent suspended from the frame using pipe clips. Lower 20 cm of the walls are made of 180 g/m² PE.</p> <ul style="list-style-type: none"> Materials: 150 g/m² polycotton – rot-proof, fire resistant CPAI 84-6 Packing: 40 kg 130 x 25 x 25 cm (bale)
Winter liner	<p>Can be hung inside the inner tent for added insulation in cold climates</p> <ul style="list-style-type: none"> Materials: 150 g/m² polycotton – rot-proof, fire resistant CPAI 84-6, white colour Packing: 40 kg 130 x 25 x 25 cm (bale)

Packing & shipping

Contents	Weight	Packing dimension	Volume
Box 1: Frame + accessories 1 Empty box weight	95.5 kg 15 kg	225 x 55 x 25 cm	1.299 m ³
Box 2: Frame + standard accessories 2 Empty box weight	115.5 kg 16 kg	225 x 55 x 30 cm	
Box 3: Main tent + ground sheet Empty box weight	115 kg 27 kg	225 x 55 x 40 cm	
Total weight (boxes stacked as one)	336 kg	225 x 55 x 95 cm	

Accessories	Weight	Packing dimension
Inner tent	29 kg	130 x 29 x 29 cm
Partition, x2	6.2 kg	130 x 14 x 14 cm
Winter liner	21.5 kg	130 x 27 x 27 cm
Lighting kit, 6 sets	4.8 kg	125 x 18 x 12 cm
Shade cover + support frame + connection flap	53 kg	150 x 50 x 45 cm

Estimated loadability¹

Estimated loadability	
Container	No. of tents
20' GP	20
40' DC	42
40' HC	42

¹ The loadability provided is based on the maximum volume and weight capacity of the containers. This might change due to road weight restrictions in the country of destination. Please contact our sales team for further clarifications.