

## Legend<sup>™</sup> 45 Tent - Fire Retardant MSF/ICRC/IFRC Standard



# Product key features Legend<sup>™</sup> 45 Tent -Fire Retardant

- MSF/ICRC/IFRC standard
- Multi-purpose tent which can be used for schooling, office, clinic, health centre, storage or temporary shelter purposes & can be attached to one another to make a longer structure
- Separate ground sheet for use in tent is available as option in case main tent is used for living conditions / clinics
- For hot climates shade net with frame is also available
  as option
- Set of 5 partitions to create separate areas and a closed cabin inside the tent is available as option
- For increase protection from heat, cold, wind, dust, and insects an Inner tent with sewed in bath tube type ground sheet is available as an option
- Suitable for 20-40 persons.

#### Dimensions

### Technical specifications

Outer tent (width x height)						
Total size	7.50 m x 6.00 m					
Ridge height	3.00 m					
Side wall height	2.10 m					

Inner tent (width x height)					
Total size	7.20 m x 5.70 m				
Ridge height	2.80 m				
Side wall height	1.95 m				

#### **Materials**

- All our materials are waterproof, rotproof and fire retardant <sup>1</sup>
- Marking and logo customised to your requirements.

- 1 Pass CPAI section 5 and 6 as per UNHCR standard with maximum 10s after flame average and maximum 30s after flame per test piece
- Ageing under ISO 4892-2, type A, 360 hours.

Materials		Tent parts							
Outer tent Roof, wall: Poly-Cotton blended fiber yarns, 440 gsm for the roof, 320gsm in finished state for the		Doors		One door on each end with fast opening/closing system and one on each side. Full width opening possible on both ends					
		oof, 320gsm	Ventilation		Two high ventilation windows with sun-visors/ shutters, grill and mosquito netting on each side. One high ventilation window with shutter, canopy/sun-visor and mosquito netting on each gable				
Mud flaps	walls    PVC coated fabric polyester 1100 dtex, PVC coated 2 sides 540 gsm		Frame		The tent has an aluminum frame with 40 mm x 2 mm pipes (same length) and steel connectors (same angle)				
			Accessories		One tent with all accessories packed in a bale. Other required accessories including assembling instruction, content list and repair kit included.				
Packing & sh	Others	Others Velcro strips on both sides for logo attachment and two electric cable passages					assages		
Content per package (packed in five separate bags)		Package A	Pac		kage B	Package C	;	Package D	Package E
		Main tent (flysheet , () frame and accessories)		Grou	und sheet	Shade net + Frame		Four room partitions and one curtain partition	Inner tent with attached ground sheet
104.5 k		Fly sheet Outer 104.5 kg, frame accessories: 11	ne +		g	28 kg		14 kg	58.3 kg
ac		Flysheet, frame accessories: 2 <sup>-1</sup> 45 cm / 0.851 c	s: 210 x 90 x 0.0		x 25 x 18 cm / 43 cbm	190 x 42 x 42 cm / 0.335 cbm		165 x 20 x 20 cm / 0.066 cbm	200 x 35 x 35 cm / 0.245 cbm
					Estimated loa	adability <sup>2</sup>		- -	
			empty cage is 130 x 90 x 114 cm and loaded 90 x 114 cm). Each item per container.				Without cage		
			ndwich Package): 24 pieces, Ground Sheet: 2 Net: 108 pieces, Partitions: 240 pieces, Inne s				Main Tent (Sandwich Package): 24 pieces, Ground Sheet: 375 pieces, Shade Net: 125 pieces, Partitions: 425 pieces, Inner Tent: 125 pieces		
40' GP contain	0' GP container Main Tent (Sandwich Package): 48 pieces, Ground Sheet: 480 pieces, Shade Net: 216 pieces, Partitions: 480 pieces, Inner Tent: 192 pieces						Main Tent (Sandwich Package): 52 pieces, Ground Sheet: 800 pieces, Shade Net: 180 pieces, Partitions: 900 pieces, Inner Tent: 252 pieces		
40' HC container Main Tent (Sandwich Package): 48 pieces, Ground Sheet: 48 pieces, Shade Net: 216 pieces, Partitions: 480 pieces, Inner Tent: 192 pieces						Main Tent (Sandwich Package): 52 pieces, Ground Sheet: 880 pieces, Shade Net: 216 pieces, Partitions: 1000 pieces, Inner Tent: 280 pieces			

<sup>2</sup> The loadability provided is based on the maximum volume and weight capacity of the containers. This might change due to road weight restrictions in the country of destination. Please contact our sales team for further clarifications.