

## Viva<sup>™</sup> Family Tent (Fire Retardant) UNHCR Standard



## Product key features Viva<sup>™</sup> Family Tent (Fire Retardant)

- UNHCR standard
- Fire retardant, waterproof, rotproof and UV-stabilised
- 16 m2 main floor area plus two 3.5 m2 vestibules for a total area of 23 m2, double-fly with ground sheet
- Complies to recommended minimum living area in hot and temperate climates (3.5 m2 per person), providing extra space for cold climates
- Suitable for family of five people.

Technical specifications

## **Dimensions**

Outer tent				
Total living area	23 m2			
Main floor	16 m2			
Two Vestibule area	3.5 m2 x 2 = 7 m2			
Centre height	2.20 m			
Width	4.00 m			
Ridge length	4.00 m			
Side wall height	1.25 m			
Centre base length	6.60 m			

Tent	doors (width and height)	Upright poles		Side poles	
Total size	1.30 m x 1.40 m	2 upright poles	2.20 m	6 side poles	1.25 m
Door flaps	1.40 m x 1.60 m	1 Centre upright pole	2.17 m	4 door poles	1.40 m
Upper part	1.40 m x 0.90 m (PC)		2.17 111		
Lower part	1.40 m x 0.70 m (PE)	Pole diameter	25 x 1.20 mm	Pole diameter	19 x 1.25 mm

Materials • All our materials are UV-proof, waterproof, rotproof and fire retardant<sup>1</sup>

• Marking and logo customised to your requirements.

Materials		Tent parts	
Outer tent	Roof: 380 gsm Polycotton, natural white (±10%) Wall: 250 gsm Polycotton, natural white (±10%)	Inner partition	Two half partitions running from Centre pole to side wall
Inner tent	160 gsm Polycotton, natural white	Chimney	A chimney reinforcement with a non-perforated opening is placed at 0.50 m from one corner
Mud flaps	180 gsm Polyethylene (HDPE), black (±5%)	Windows	Outer tent has two long windows (360 x 30 cm) with mosquito netting and a rain flap running on both sides of the tent
Ground sheet	180 gsm Polyethylene (HDPE), black, sewn in bathtub (±5%)	Ventilators	The outer tent has two ventilation openings (25 x 30cm) in front and back with reinforcement netting and a rain flap.

## Packing & shipping

Packing information		
Content per tent bale	Tent, inner tent, accessories (assembly instruction, content list and repair kit)	
Weight per tent	67-68 kgs approx.	
Dimension per tent	225 x 35 x 35 cm	
Volume per tent	0.276 cbm	
Number of tents per cage	15	
Dimension per cage	230 x 117 x 113 cm	
Volume per cage	3.04 cbm	
Weight per cage	1,045 kgs approx.	

Estimated loadability <sup>2</sup>				
Container	With cage	Without cage		
20' GP container	10 cages, 120 tents	130 tents		
40' GP container	20 cages, 240 tents	290 tents		
40' GP container	20 cages, 240 tents	340 tents		

 <sup>1</sup> Pass CPAI section 5 and 6 as per UNHCR standard with maximum 10s after flame average and maximum 30s after flame per test piece

• Ageing under ISO 4892-2, type A, 360 hours.